

# FINISHING GUM

---

## TECHNICAL SPECIFICATIONS

Description	FINISHING GUM is manufactured by MyLan Group. This product is formulated to use with Graphic Arts product, all CTP plates and Negative plates. FINISHING GUM will protect coatings for the plates in storage.
Compositions	FINISHING GUM contains water, acidic solution containing organic salts, anti-odor agents.
Usage	Dilute 40 to 60% of FINISHING GUM with tap water. It can be used directly with the automatic dilution systems equipped with plate processors.
Specifications	pH value between 3 to 4 at 25°C
Safelight	None required - daylight handling
Shelf life	12 months under recommended storage conditions
Packaging	10, 20 liters
Transport and storage	Should be stored flat and away from excessive cold, heat and humidity. Use in a controlled environment of 5°C – 30°C and 40 – 80% RH, non-condensing
Availability	Contact your local MyLan Group representative. See the list of our Distributors at <a href="http://www.mylangroup.com">www.mylangroup.com</a> for contact information.



### MYLAN GROUP

LongDuc Industrial Park, TraVinh City, TraVinh Province, Vietnam  
Tel: +84-74-3846 997 Fax: +84-74-3846 998  
Email: [info@mylangroup.com](mailto:info@mylangroup.com)  
Website: [www.mylangroup.com](http://www.mylangroup.com)

